

C190

Tall and wide with high transparency
New minimal profile design
High security for prestigious entrances

DIMENSIONS

External Diameter:	1911 mm
Internal Diameter:	1760 mm
Entrance Width:	1200 mm
Internal Height:	2300 mm
External Height:	2460 mm
Overall Height:	2530 mm

PORTAL WEIGHT GUIDELINE

Portal weight with different glass type (it may change upon portal configurations).

Typical portal guideline: 1380 - 2000 Kg

POWER SUPPLY

Input:	110/230 VAC (EMI Filter included)
Output:	13/24 Vdc, 5/7 A/hour
Average Power consumption:	35 watt (per hour of continuous operation)
Max Power Rating:	150 watt
Emergency Battery Back-up:	6-8 hours

MOTORS


Reversible motors with permanent magnet, working power of 24 Vdc, provided with an encoder for the continuous control of the door position. Doors are provided with electronic control of motor torque for door safety stop in presence of an obstacle.

AVAILABLE CERTIFICATED LEVELS

PRODUCT NAME	SECURITY RATING	CERTIFICATION REF. NUMBER	TYPE OF GLASS
C190-S1	SR1	1479a/01	Vandal resistant: P4A EN 356
C190-S2	SR2	1479a/02	Vandal resistant: P4A EN 356 Attack resistant: P8B EN 356 Bullet resistant: BR3/S EN 1063
C190-S3	SR3	1479a/03	Attack resistant: P8B EN 356 Bullet resistant: BR3/S EN 1063



C190-S1 to S3 Portals
Approved to LPS1175: Issue 7
Security Ratings 1 to 3
Cert/LPCB Ref. 1479a



ALLUSER INDUSTRIE SRL

T. +39 0490991800
E. alluser@alluserindustrie.com
W. alluserindustrie.com

FEATURES

VERSIONS

- S version: welded portal structure with 70 mm floor base (recessed or surface mounted).
- R version: rail floor guide 12 mm base. (surface mounted installation only).
- K version: cabin delivered to be assembled at the installation site.
- C190-S1 Approved to LP1175: issue 7 SR1
- C190-S2 Approved to LP1175: issue 7 SR2
- C190-S3 Approved to LP1175: issue 7 SR3

DIRECTION

- Entrance Direction: Straight
- × Entrance Direction: 90 degrees Left
- × Entrance Direction: 90 degrees Right.
- × Entrance Direction: 45 degrees

OUTER FINISHING

- Outer Finishing: RAL colours (sliding door frames RAL 9005 - Black).
- Polished Steel
- Brushed Steel
- Aluminium

DETECTION DEVICES

- Infrared Presence Sensor.
- Pressure mat for presence person
- APD - Anti Piggybacking Device
- 2 zone contact mat
- × Metal Detector
- Reed Door Position Tamper Sensor: EN 61000-6-3:2007+A1:2011, EN 50130-4:2011, EN50131-2-6:2008

STRUCTURE

- Certificated metal Top Canopy in accordance with FB2/NS EN 1522
- Certificated metal portal structure in accordance with FB4/NS EN 1522.
- Anti-slip floor mat EN13893. Fire reaction in accordance with Bfls1 N13501-1
- × Extra glazing on the flat sliding door pocket structure
- Floor Pan (for S version only)

EXTENSIONS

- 2030 mm Internal Portal Height.
- 2135mm Internal Portal Height.
- 2300 mm Internal Portal Height.
- × Portal length extension

SAFETY

- Infrared Safety Sensor.
- Fire Alarm Signal opens secure and/or non secure side.
- Rescue Push Button to open the portal door which last closed and safely exit the portal.
- Curved sliding Doors: Fail Safe

CONTROLLERS

- LED traffic light on secure and non secure side
- Standard Intercom (PPT - PushPerTalk) [from control panel to non secure side traffic light]
- Multi-function Control Panel for remote control of the Portal with 15 m cable
- Service Mode Key switch: Local ON / OFF key switch selector and cleaning mode function.
- Additional Multi-function Control Panel for remote control of the Portal.
- Web lan control
- × Emergency Door Control Panel (for emergency swing door management)

ELECTRONICS

- Alluser Interlocking Door System Control Motherboard with APS (Alluser Portal Software).
- Nominal power consumption 35 W.
- Emergency battery backup; 6-8 hrs, in standard configuration.
- Internal 24V DC LED Light. (warm white 3.000 K; life expectancy 50.000 h)
- Nominal 24 VDC 5A Power Supply, with Battery Backup Charger; Input 110-230VAC (EMI Filter included)

DOORS

- Bi-Parting (2 doors open on each side)
- × Sliding Doors centre frame overlapping edge (to be used for BR glazing).
- × Both doors slide to open on the same side.
- Curved sliding Doors: Fail Secure

EMERGENCY UNLOCKING DEVICES

- Secure side mechanical emergency unlocking device.
- × 90 degrees emergency lever
- extra emergency lever
- × Manual Panic break out opening. In emergency, the automatic flat sliding doors can be opened by pushing them.

TOP & NIGHT

- Locked Top cover.
- Night Lock
- Fiberglass Rain Cap top cover
- First & Last Transit with 7 Mechanical Keys
- First-last transit, with 7 proxy keys